



DSS424S-D5

Key Features:

- Storage server supports Dual Intel® Xeon® SP Skylake up to 1.5TB DDR4 RAM
- Four hot-swappable 60mm fan modules per motherboard module
- Support two hot-swap MB Modules each with Xeon® DP server boards in one system as unified redundant controllers
- HA Redundant Cluster-in-a-Box solution with PCIe NTB and GigE heartbeat
- 4U with 24x 3.5" 12Gbps SAS hot-swap HDD bays



Specifications

Processor Support	Each Node: Supports Intel® Xeon® SP Skylake up to 205W TDP socket LGA3647	Supported OS	Windows 2012 R2, RHEL 6.5, SLES 11 SP3, Windows 2008 R2, VMWare ESXi 5.5, FreeBSD 9.2 Centos 6.5; For other OS please contact us
Chipset	Intel® C621 chipset	Front Panel	Power On/OFF with LED, reset Switch, NMI switch, Locate Switch with LED, 4xLAN LED, Warning LED
Memory Support	Each Node: Supports up to 16x DIMMs DDR4 RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 2666	Rear I/O	Each Node: 3x USB 2.0 ports; 4x USB 3.0 ports; 1x VGA port, VGA, 2x GbE RJ45, 1x GbE IPMI
Expansion Slot	Each Node: 4x PCIe Gen3 x16 slots; 3x PCIe Gen3 x8 slots	Cooling	Each node: 4x 60mm fans
Storage	Each node: 36 ports 12G SAS Expander with 3 SFF8643 Connectors	Other Features	Dedicated GbE for IPMI 2.0
Drive Bays	24 hot-swap 3.5" 12G/6G SAS/SATA drive bay Each node: 2x internal 2.5" 7mm for OS drive bays	Weight	Gross: 51.78KG/114LBS; Net: 33.9KG/75LBS
Network	Each Node: 2x GbE ports, 1x GbE dedicated for IPMI	Dimension	System: 27"x19"x7" (DxWxH) Packaging: 38"x 25.2"x18"(LxWxH)
Power	1+1 1200W aC/DC 80 Plus Redundant PSU under 220V AC; optional -48V DC input available upon request	Logistic	HTS Code: 8473 30 5100; ECCN: 4A994
		Environmental	Operating Temperature: 0°C to 35°C Non-Operating Temperature: -20°C to 70°C Humidity: 5% to 95% non-condensing
		Compliance	CE, FCC Class A, RoHS 6/6 compliant

Ordering Information

BB42433D5TY18 DSS424S-D5 DP BB server, 1200W RPSU, 12G expander, Rev. A