



## OSS212L-D5 (Low Profile)

### Key Features:

- 2U 26" in-depth storage appliance server chassis
- 12 Tray-less Hot Swap 3.5" 12G SAS/SATA drive bays & two 2.5" internal bay
- Supports Intel® Xeon ATX, 10.5" SSI CEB or 13" EEB motherboards
- 7 low profile expansion slots
- High efficiency Platinum 550/800/1200W redundant power



## Specifications

<b>Processor Support</b>	Supports Dual Intel® Xeon® SP (Skylake) up to 205W TDP socket LGA3647	<b>Supported OS</b>	Windows 2012 R2, RHEL 6.5, SLES 11 SP3, Windows 2008 R2, VMWare ESXi 5.5, FreeBSD 9.2 Centos 6.5; For other OS, please contact us.
<b>Chipset</b>	Intel® C621 chipset	<b>Front Panel</b>	2 x 5 header; Power On/Off with LED, Reset Switch, NMI switch, Locate Switch with LED, 4x LAN LED Status/Warning LED
<b>Memory Support</b>	Supports 12x DDR4 RDIMM/LRDIMM (3DS) 2133/2400/2666 MT/s	<b>Rear I/O</b>	4x USB 3.0; 1x D-Sub 15-pin VGA port; 2x RJ-45 GbE ports
<b>Expansion Slot</b>	Supports a total of 7 low profile expansion slots; 4x PCIe3 x16, 3x PCIe3 x8	<b>Cooling</b>	3 x 80mm and 2x 40mm easy swap PWM fans
<b>Storage</b>	36ports 12Gb/s SAS Expander with 3 SFF8643 ports	<b>Other Features</b>	RAID 0/1/10/5 (Intel RSTe)
<b>Drive Bays</b>	12x SAS/SATA 12G/6G tray-less 3.5" bays, 2x internal OS 2.5", Optional: 2x Rear tool-less 2.5" 7mm bays	<b>Weight</b>	Gross Weight: 23KG/50lbs Net Weight: 17KG/37.4lbs
<b>Network</b>	2x GbE ports	<b>Dimensions</b>	System: 26"x19"x3.5" (DxWxH) Packaging: 37"x25.2"x13.8"(LxWxH)
<b>Power</b>	1+1 800W or 1200W 80 Plus Redundant PSU, optional -48V DC input available upon request	<b>Logistic</b>	HTS Code: 8473 30 5100; ECCN: 4A994
		<b>Environmental</b>	Operating Temperature: 0°C to 35°C Non-Operating Temperature: -20°C to 70°C Humidity: 5% to 95% non-condensing
		<b>Compliance</b>	CE, FCC Class A, RoHS 6/6 compliant

## Ordering Information

<b>BB21233D5TY16</b>	OSS212L-D5 (low Profile) DP BB server, 800W RPSU, 12G expander, Rev. A
<b>BB21233D5TY18</b>	OSS212L-D5 (low Profile) DP BB server, 1200W RPSU, 12G expander, Rev. A
<b>BB21233D5TY16</b>	OSS212L-D5 (low Profile) DP BB server, 800W RPSU, Rev. A
<b>BB21233D5TY18</b>	OSS212L-D5 (low Profile) DP BB server, 1200W RPSU, Rev. A