



## eDrawer4060S-UN

### Key Features:

- Storage server supports single AMD EPYC (Naples)
- Support 60 x 3.5" Drive Bays in 4RU
- Two 48 ports 12G SAS expanders for maximum throughput
- Support full height PCIe expansions without risers



## Specifications

<b>Processor Support</b>	Supports Single AMD EPYC (Naples) up to 108W TDP socket SP3	<b>Supported OS</b>	Windows 2012 R2, RHEL 6.5, SLES 11 SP3, Windows 2008/2012 R2, VMWare ESXi 5.5, FreeBSD 9.2 Centos 6.5; For other OS please contact us
<b>Chipset</b>	Intel® C621 chipset	<b>Front Panel</b>	Power On/OFF with LED, reset Switch, NMI switch, Locate Switch with LED, 2x LAN LED, Warning LED
<b>Memory Support</b>	Supports up to 8x DIMMs DDR4 RDIMM/RDIMM 3DS/LRDIMM/LRDIMM 3DS 2666 up to 1TB	<b>Rear I/O</b>	2x USB 2.0 ports; 2x USB 3.0 ports; 1x VGA port(s); 1x COM Port; 2x GbE ports
<b>Expansion Slot</b>	3 PCIe 3.0 x16; 3 PCIe 3.0 x8	<b>Cooling</b>	5x 97mm exhaust blower
<b>Storage</b>	Two 48 ports SAS Expander 6 SFF8643 24 ports 12G SAS/SATA to HBA/RAID	<b>Other Features</b>	Dedicated GbE for IPMI 2.0
<b>Drive Bays</b>	60 hot-swap 3.5" 12G SAS/SATA drive bays 2x internal 2.5" 7mm for OS drive bays	<b>Weight</b>	Gross: 69Kg/152 Lbs; Net: 60Kg/132Lbs
<b>Network</b>	2x GbE ports, 1x GbE dedicated for IPMI	<b>Dimension</b>	System: 36.5"x19"x7" (LxWxH) Packaging: 47.6" x 24.8"x13.6"(LxWxH)
<b>Power</b>	2+2 1600 W AC/DC 80 Plus Redundant PSU optional -48V DC input available upon request	<b>Logistic</b>	HTS Code: 8473 30 5100; ECCN: 4A994
		<b>Environmental</b>	Operating Temperature: 0°C to 35°C Non-Operating Temperature: -20°C to 70°C Humidity: 5% to 95% non-condensing
		<b>Compliance</b>	CE, FCC Class A, RoHS 6/6 compliant

## Ordering Information

**BB46033UNS** 4U 60 BAYS 3.5" HDD 12G SAS SINGLE EPYC 1200W HRP